

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ5	10	
Φ5.2	8	
Φ5.56×2.3	7.5	
Φ6	7.5	
Φ6.35	8	
Φ6.35 记号点/实心	7.5	With a dot for marking
Φ6.38	2	
Φ6.5	2	
Φ6.5×2.2	2	
Φ7.5	10	
Φ7.5×1.2	10	
Φ7.5×3.2	10	
Φ7.6	2	
Φ8	10	
Φ8 记号点	10	With a dot for marking
Φ8 偏心记号点	10	With a dot for marking
Φ8 记号点/实心	12	With a dot for marking Φ2×1.2
Φ8 面包	8	One side is vaulted
Φ8×2.1	10	
Φ8×2.9	12	
Φ8×3	8	
Φ8×4	8	
Φ8×4.15	10	
Φ8×4.2	8	
Φ8×4.5	10	
Φ8.2	2	
Φ8.3	10	
Φ8.5	7.5	
Φ8.5 记号点	7.5	With a dot for marking
Φ8.5×5.2 记号点	7.5	With a dot for marking
Φ9.4	8	
Φ9.4×4	8	
Φ9.4×5	8	
Φ9.4×6.2	8	
Φ9.4记号点	8	With a dot for marking
Φ10	10	
Φ10.1×7	10	
Φ10.5	10	
Φ10.5×6.5	10	
Φ10.5记号点	10	With a dot for marking
Φ10.8	7.5	
Φ10.8×7.62	7.5	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ10×3	10	
Φ10×3.2沉头孔	10	with countersunk hole
Φ10×3.5	10	
Φ10×4	10	
Φ10×4.5	10	
Φ10×5	10	
Φ10×5.5	10	
Φ10×6	10	
Φ10记号点	10	With a dot for marking
Φ11.5	10	
Φ11.5×4.2	5	
Φ11.5×4.3	10	
Φ11.5×5	5	
Φ11.6×4	7.5	
Φ11.6×4 记号点	10	with a dot for marking
Φ11×6	5	
Φ12	10	
Φ12 记号点	10	Φ2×1.5
Φ12 面包	10	One side is vaulted
Φ12.5	4	
Φ12.5 记号点	4	with a dot for marking
Φ12.5×3.5	4	
Φ12.5×4.1	8	
Φ12.5×6.4	4	
Φ12.5×7.5	4	
Φ12.5×8.5	4	
Φ12×3	10	
Φ12×4	10	
Φ12×4.5	10	
Φ12×5	10	
Φ12×F3	10	with a square countersunk hole
Φ13	8	
Φ13 记号点	8	with a dot for marking Φ2.5×1.6
Φ13大记号点	8	with a dot for marking Φ3.2×0.56
Φ13.1×2.6	8	
Φ13.1×2.6/实	8	with a dot for marking
Φ13.3×3.25	10	
Φ13.5	7.5	
Φ13.5 记号点	10	with a dot for marking
Φ13.5×3.43	7.5	
Φ13.5×5	7.5	
Φ13.5×5.35	7.5	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ13.5×5.5	10	
Φ13.5×6.1	10	
Φ13.5×6.4	10	
Φ13.5×6.78	7.5	
Φ13.5×8.1	7.5	
Φ13.8	7.5	
Φ13.8×5	8	
Φ13.8×5.5	7.5	
Φ13×2.6	8	
Φ13×3.2	8	
Φ13×3.4	8	
Φ13×7.2	8	
Φ13×7.34	8	
Φ13大记号点	8	with a dot for marking
Φ14	8	
Φ14.1	10	
Φ14.1	17.5	only 17.5mm
Φ14.1×4.2	10	with a countersunk hole
Φ14.1×5.2	10	
Φ14.2	17	
Φ14.3×24.5 (径向转子)		Groove (2*R1.5)
Φ14.5×10.5	10	
Φ14.5×F3.3×3.3	10	with a square hole
Φ14×2	8	
Φ14×3	8	
Φ14×3.5	8	
Φ14×4	8	
Φ14×6	8	
Φ14×9	10	
Φ14×9.5	8	
Φ15	10	
Φ15×3.2 面包		One side is vaulted
Φ15×5	8	
Φ15×6	8	
Φ15×6.5	8	
Φ15×9.5	8	
Φ15×10	8	
Φ15记号点	8	with a dot for marking
Φ15面包	8	One side is vaulted
Φ15.2	10	with a countersunk hole(Φ8)
Φ15.2×10.5	10	
Φ15.2×3	10	with a countersunk hole(Φ8)

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ15.2×3.2	10	with a countersunk hole(Φ8)
Φ15.2×4.5	10	with a countersunk hole(Φ8)
Φ15.2×6.25	10	with a countersunk hole(Φ8)
Φ15.2×Φ7	10	中孔带凹线
Φ15.6	5	
Φ15.6 记号	5	
Φ15.6×10.8	5	
Φ15.6×3.2	5	
Φ15.6×5.5	5	
Φ15.6×7	5	
Φ16	10	
Φ16×10	4	
Φ16×11	10	
Φ16×4.3	5	
Φ16×4.6	8	
Φ16×6.5	10	
Φ16×7	10	
Φ16×9	5	
Φ16记号点	10	with a dot for marking
Φ16.2×5.8	8	
Φ16.2×6	8	
Φ16.2×7.5	8	
Φ16.25×11.2	10	
Φ16.3	10	
Φ16.3×6.25	10	
Φ16.3×6.5	10	
Φ16.3×8	10	
Φ16.3×8.5	10	
Φ16.3偏心记号点	10	with a dot for marking
Φ16.7/记号点	10	with a dot for marking
Φ16.7×11.5	10	
Φ16.7×9.9	10	
Φ17	8	
Φ17.5	8	
Φ17.5×10.9	8	
Φ17.5×13	8	
Φ17.5×4.2	8	
Φ17.5×4.2内倒角沉头9.6+0.5	8	inner chamfer and countersunk hole
Φ17.5×5.4	7.5	
Φ17.5×7.1	8	
Φ17.5×7.2	8	
Φ17.5×7.5	8	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ17.5×7.5	-1	
Φ17.5×7.5面包	7.5	One side is vaulted
Φ17.5×9.1	7.5	
Φ17.5记号点	8	with a dot for marking
Φ17×13	8	
Φ17×8.45	8	
Φ18	10	
Φ18 ×3.4	7.5	
Φ18.5		
Φ18.5×6		
Φ18.5×7		
Φ18.6×6	10	
Φ18.6×6.6	10	
Φ18.6×7	10	
Φ18.6记号点	10	with a dot for marking
Φ18.6圆饼	10	
Φ18.8		
Φ18×11.4	7.5	
Φ18×12.5	7.5	
Φ18×5记号点	10	with a dot for marking
Φ18×6.6	5	
Φ18×7	10	
Φ18×8	5	
Φ18×8.4	7.5	
Φ18×9.6	5	偏心0.125
Φ18×9.6	10	偏心0.2
Φ18×9记号点	7.5	with a dot for marking
Φ18记点Φ8×90	10	with a dot for marking (Φ8×90)
Φ18记号点	10	with a dot for marking
Φ18记号点		with a dot for marking
Φ19	10	
Φ19.5	10	
Φ19.5×5.5	10	
Φ19.55×10	7.5	
Φ19.5记号点	10	with a dot for marking
Φ19.9×6	10	
Φ19×11	10	
Φ19×11.4	10	
Φ19×12	10	
Φ19×13	10	
Φ19×6.1	10	
Φ19×6.5	10	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ19.8	2	
Φ20	10	
Φ20 面包	7.5	One side is vaulted
Φ20X6.2	4	only 4mm
Φ20.2×14.6	7.5	
Φ20.25	2	
Φ20.3/记号点	7.5	with a dot for marking
Φ20.3×10	7.5	
Φ20.3×12.7	7.5	
Φ20.3×4	7.5	
Φ20.3×6	7.5	
Φ20.3×7.2	7.5	
Φ20.3×7.5	7.5	
Φ20.3×8	7.5	
Φ20.3×8.5	7.5	
Φ20.3×9.4	7.5	
Φ20.3记号点	10	with a dot for marking
Φ20.3实/记号点	7.5	with a dot for marking
Φ20.3实心	10	with a dot for marking
Φ20.4	2	
Φ20.5	10	
Φ20.5×5.5	10	
Φ20.5记号点	10	with a dot for marking
Φ20.9×12	8	
Φ20×10	7.5	
Φ20×10 (记)	7.5	with a dot for marking
Φ20×10.5	7.5	
Φ20×11.2	10	
Φ20×12.5	7.5	
Φ20×13.3	10	
Φ20×14.5	7.5	
Φ20×2.5	7.5	
Φ20×3.5 (S标记)	7.5	with a S marking
Φ20×3.5沉头孔Φ10.5×3.25	7.5	with a countersunk hole (Φ10.5×3.25)
Φ20×4	7.5	
Φ20×4.3	7.5	
Φ20×4.3/Φ20×4.3沉头孔	10	with a countersunk hole
Φ20×4.3沉头孔带S标记	10	with a countersunk hole and S
Φ20×4.5/Φ20×5	10	
Φ20×4.6	10	
Φ20×5	10	
Φ20×5.2(特殊沉头) 一端平面沉头	10	with a special countersunk hole

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ20×5.3	10	
Φ20×5.5 (内倒角)	10	inner chamfer
Φ20×6.2	7.5	
Φ20×6.5	10	
Φ20×7.2	10	
Φ20×7.5 面包	10	One side is vaulted
Φ20×8	7.5	
Φ20×Φ7.5 面包磁	7.5	One side is vaulted
Φ20×Φ6.2	10	
Φ20单面倒角	10	1.9×45°
Φ20记号点	10	with a dot for marking
Φ20面包	10	One side is vaulted
Φ21	8	
Φ21.4	8	
Φ21.4×10.4	8	
Φ21.4×12.3	8	
Φ21.4×12.5	8	
Φ21.4×13	8	
Φ21.4×5.5	8	
Φ21×12	8	
Φ21×13	8	
Φ21×5.5	8	
Φ21记号点	8	with a dot for marking
Φ22	10	
Φ22.3	10	
Φ22.3×14.7	10	
Φ22.3×16	10	
Φ22.3记号点	10	with a dot for marking Φ3×1.5
Φ22.5×10	10	
Φ22.6	2	
Φ22.7	2	
Φ22.9×4.65沉头孔	10	with a countersunk hole
Φ22×10	10	
Φ22×12	10	
Φ22×12.2	10	
Φ22×15	10	
Φ22×16	10	
Φ22×5.5	10	
Φ22面包	10	One side is vaulted
Φ23	10	
Φ23.1	7.5	
Φ23.1×12.5	7.5	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ23.3记号点	2	with a dot for marking
Φ23.4	10	
Φ23.8×10	10	
Φ23.8×14	10	
Φ23.8×14.5	10	
Φ23.8×16	10	
Φ23.8×17	10	
Φ23.8×5	10	
Φ23.8实/记号点	10	with a dot for marking
Φ23/记号点	10	with a dot for marking
Φ23×12.5	10	
Φ23×13	10	
Φ23×16.5	10	
Φ23×4.3	10	
Φ23×4.4	10	
Φ23×5.3	10	
Φ23×6.5	10	
Φ23记号点	10	with a dot for marking
Φ24	10	
Φ24.2	10	
Φ24.2×10.2	10	
Φ24.2×F15×8	10	
Φ24.5XΦ5.3	14.5	
Φ24.9	10	
Φ24.9×8	10	
Φ24.9记号点	10	with a dot for marking
Φ24×15.5	10	
Φ24记号点	10	with a dot for marking
Φ25	14.5	
Φ25 ×10	8	
Φ25.3	8	
Φ25.3 ×13	8	
Φ25.3 ×17	8	
Φ25.3×6	8	
Φ25.3×7.2	8	with a countersunk hole (Φ12)
Φ25.3×7.5	8	
Φ25.4	8	
Φ25.4×11	8	
Φ25.4×12.4	8	grooves along the outer ring
Φ25.4×12.7	10	
Φ25.4×13	8	
Φ25.4×15.2	8	中孔带凹线R角

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ25.4×15.2	10	
Φ25.4×15.5	8	
Φ25.4×15.9	10	
Φ25.4×5	8	
Φ25.4×6	10	
Φ25.4×8	8	
Φ25.4×9.5	10	
Φ25.8		
Φ25.8记号点		with a dot for marking
Φ25.9	10	
Φ25.9×10	10	
Φ25.9×12.1	10	
Φ25.9×12.2	10	
Φ25.9×13.46	10	
Φ25.9×22.5	10	
Φ25×10	8	
Φ25×11	14	
Φ25×15	8	
Φ25×16	8	
Φ25×3.2	8	
Φ25×5	8	with a countersunk hole (Φ10.6×7.8)
Φ25×6	14	
Φ25×7	10	
Φ25×7.5	14	
Φ25x(d7x5) 椭圆孔	10	with a oval hole
Φ25记号点	14.5	with a dot for marking
Φ25外倒角	14.5	outer chamfer
Φ26.5×19	10	
Φ26.5记号点	8	with a dot for marking
Φ26×12.5	10	
Φ27	10	
Φ27 记号点/实心		with a dot for marking
Φ27 记号点/实心	8	with a dot for marking
Φ27.2×16.1	8	
Φ27.9×14	10	
Φ27.9×16.1记号点	10	with a dot for marking
Φ27.9×17.3记号点	10	with a dot for marking
Φ27.9×5	10	
Φ27.9×5.5	10	
Φ27.9√	10	
Φ27×12.5		
Φ27×12.5	10	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ27×13	8	
Φ27×17	10	
Φ27×17.8	8	
Φ27×19	8	
Φ27×19.9		
Φ27记号点	10	with a dot for marking
Φ28	10	
Φ28.6	10	
Φ28.6×10	10	
Φ28.6×13	10	
Φ28.6×15.5	10	
Φ28.6×5.4	10	
Φ28.6√	10	
Φ28.6记号点	10	with a dot for marking Φ2×1.5
Φ28×6.5	10	with a countersunk hole (Φ17.05)
Φ28xΦ6.5x10沉头	10	
Φ28记号点	10	with a dot for marking
Φ29.5×10	10	
Φ29.5×13	10	
Φ29.5×14	10	
Φ29.5×15	10	
Φ29.5×16.5	10	
Φ29.5×21	10	
Φ29.5×23.9	10	
Φ29.5×5.5	10	
Φ29.5×8.4	10	
Φ29.5×9.5	10	
Φ29.5√	10	
Φ29×Φ10	10	
Φ30	15	
Φ30 实心	7	with a dot for marking
Φ30.3/记号点/实	10	with a dot for marking
Φ30×10	7	
Φ30×12	10	
Φ30×12.5	7	
Φ30×13	7	
Φ30×16	7	
Φ30×16.3记号点	10	with a dot for marking
Φ30×18	10	
Φ30×19.5	7	
Φ30×20	10	
Φ30×24	10	

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ30×6	7	
Φ30×8	7	
Φ30×9	7	
Φ30×Φ12.5	15	
Φ31×18	6	only 6mm
Φ31.242×22.479	10	
Φ31.2实/记号点	10	with a dot for marking
Φ31.75×Φ9.525	10	
Φ32	10	
Φ32×Φ18	10	
Φ32×Φ23	10	
Φ32×Φ5.5沉头孔	10	with a countersunk hole
Φ32×Φ8.5	10	
Φ33×Φ21	10	
Φ34	10	
Φ34×22	10	
Φ34×24	10	
Φ34带记号点	10	with a dot for marking
Φ35	7.5	
Φ35×10	7.5	
Φ35×20记号点	7.5	with a dot for marking
Φ36	10	
Φ36.5×5.5	10	
Φ38	12	
Φ38×20.2	10	
Φ38×22	12	
Φ38×24	12	
Φ38×24.5	10	
Φ38×27	12	
Φ38×32.5	12	
Φ38实/记号点	10	with a dot for marking
Φ39×23(63T)	8	three holes (Φ3.7)
Φ40	10	
Φ40×14.2	10	
Φ40×33	10	
Φ41.6×5	10	
Φ42	10	
Φ42×30	10	
Φ44.5×22	10	
Φ44.5×22记号点	10	with a dot for marking
Φ44.5×32.5	10	
Φ44.5实	10	with a dot for marking

FST Cylinder,Disc and Ring Specification Table(Wet Press)

Specification (mm)	Maximum Thickness (mm)	Remark
Φ45	10	
Φ45.5×12.5	10	
Φ45.5×14	10	
Φ45.5×16.7	10	
Φ45×14.3	10	
Φ45×14.3记号点	10	with a dot for marking
Φ45×22	10	
Φ45×28	10	
Φ45×29.5	10	
Φ49×37	10	
Φ50×35	10	
Φ52×14	10	
Φ53×18记号点	10	with a dot for marking
Φ53×28	10	
Φ56×33.5		three holes (Φ5.4)
Φ56×33.5×4.5	10	three holes
Φ58×43.5	14	
Φ62×43.5	14	
Φ64.7×25	10	
Φ67.6×50	14.5	
Φ68.5×45		three holes (Φ5.4)
Φ68×25	10	带R角
Φ86×45马蹄形		horseshoe shape
Φ86.5×45马蹄形		horseshoe shape
Φ89.5×50	8	Only 8mm
Φ90×50		
Φ90×55		three holes (Φ6.1)
Φ104×71实		with a dot for marking
Φ104×71		three holes (Φ7.1)
Φ134×89		three holes (Φ11.2)
Φ160×25(厚)		